



ITALIAN SHOWER

Water in Motion  

RACCORDI IN OTTONE A PRESSARE | BRASS PRESS FITTINGS



100% MADE IN ITALY | THE ITALIAN HIGH QUALITY

RACCORDI IN OTTONE ASSIALI

I Raccordi assiali in ottone sono progettati per il collegamento dei tubi in polietilene reticolato (PEX) e in polietilene di elevata resistenza termica (PE-RT). I raccordi sono idonei sia per il passaggio di acqua calda che fredda in impianti idrico sanitari, impianti di riscaldamento a radiatori e pannelli radianti o sistemi di raffrescamento. Essi consentono la posa della tubazione sia a cielo aperto che sottotraccia. Grazie al montaggio dei raccordi assiali si realizza una connessione stabile a tenuta stagna, senza utilizzo di o-ring aggiuntivi, il quale non richiede manutenzione.

Il montaggio del tubo all'esterno del raccordo viene effettuato attraverso un'attrezzatura manuale di facile utilizzo, che attraverso uno svasatore "allarga" le estremità del tubo e lo calza sul raccordo. Il tubo sul raccordo viene poi serrato dalla presenza della bussola del diametro adeguato.

Le principali caratteristiche dei raccordi assiali sono le seguenti: durata nel tempo, maggior passaggio di acqua, resistenza alle alte temperature e versatilità.

BRASS AXIAL FITTINGS

Brass axial fittings are designed for connecting cross-linked polyethylene (PEX) pipes and high-temperature resistant polyethylene (PE-RT) pipes. The fittings are suitable for both hot and cold water in hydro-sanitary systems, radiator and underfloor heating systems, or cooling systems. They allow for the installation of piping both above ground and underground. Thanks to the installation of axial fittings, a stable and watertight connection is achieved without the use of additional O-rings, which does not require maintenance.

The installation of the pipe outside the fitting is carried out using an easy-to-use manual tool, which, through a reamer, "widens" the ends of the pipe and fits it onto the fitting. The pipe on the fitting is then tightened by the presence of the appropriately sized sleeve.

The main characteristics of axial fittings are as follows: durability over time, greater water flow, resistance to high temperatures, and versatility.



2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
BUSSOLA PER RACCORDI ASSIALI <i>SLEEVE FOR AXIAL FITTINGS</i>	16 20 25 32
	
ARTICOLO ITEM	MISURA SIZE
MANICOTTO DI RIDUZIONE <i>REDUCING COUPLING</i>	20 x 16 25 x 16 25 x 20 32 x 25 32 x 20
	

ARTICOLO ITEM	MISURA SIZE
MANICOTTO <i>COUPLING</i>	16 x 16 20 x 20 25 x 25 32 x 32
	
ARTICOLO ITEM	MISURA SIZE
RACCORDO MASCHIO <i>MALE ADAPTOR</i>	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 1/2" 25 x 3/4" 25 x 1" 32 x 3/4" 32 x 1"
	

2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
RACCORDO FEMMINA <i>FEMALE ADAPTOR</i> 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1" 32 x 3/4" 32 x 1"
ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° CON DERIVAZIONE FEMMINA <i>90° ELBOW WITH THREADED FEMALE TAKE OFF</i> 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1"

ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° CON DERIVAZIONE MASCHIO <i>90° ELBOW WITH THREADED MALE TAKE OFF</i> 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1"
ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° <i>90° ELBOW</i> 	16 x 16 20 x 20 25 x 25 32 x 32

2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
TEE A 90° 90° TEE 	16 x 16 20 x 20 25 x 25 32 x 32
ARTICOLO ITEM	MISURA SIZE
TEE A 90° RIDOTTO 90° REDUCING TEE 	16 x 20 x 16 20 x 16 x 16 20 x 20 x 16 25 x 16 x 16 25 x 16 x 20 25 x 20 x 16 25 x 16 x 25 20 x 25 x 20 25 x 20 x 20 25 x 25 x 16 25 x 20 x 25 25 x 25 x 20 32 x 16 x 32 32 x 20 x 32 32 x 25 x 32

ARTICOLO ITEM	MISURA SIZE
TEE A 90° CON DERIVAZIONE FEMMINA 90° TEE WITH THREADED FEMALE TAKE OFF 	16 x 1/2" x 16 20 x 1/2" x 20 20 x 3/4" x 20 25 x 3/4" x 25
ARTICOLO ITEM	MISURA SIZE
RACCORDO MURALE A GOMITO WALL PLATE ELBOW FITTING 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4"

2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
RACCORDO FEMMINA CON DADO GIREVOLE FEMALE FITTING WITH ROTATING NUT	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1" 32 x 1"
	

ARTICOLO ITEM	MISURA SIZE
DRITTO CON DADO GIREVOLE EUROKONO DIRECT FITTING WITH ROTATING NUT EUROKONO	16 x 3/4" 20 x 3/4"
	



ITALIAN SHOWER

Water in Motion 

Italian Shower Srl

Via Edison, 27 - 27/a
25050 Provaglio d'Iseo (BS) - Italy

P.iva e C.F. 03524420985

Tel. +39 030/6950257 | Fax +39 030/6950258

Informazioni: info@italianshower.com

Export: export@italianshower.com

PEC: italianshower@legalmail.it

www.italianshower.com

www.italianshower.it

