



ITALIAN SHOWER

Water in Motion 

CATALOGO PRODOTTI | PRODUCTS CATALOG



INDICE | INDEX

1	PRESENTAZIONE AZIENDALE	
	<i>COMPANY PROFILE</i>	4
2	RACCORDI IN OTTONE	
	<i>BRASS FITTINGS</i>	6
	2.1 RACCORDI FILETTATI	
	<i>BRASS THREADED FITTINGS</i>	7
	2.2 RACCORDI A PRESSARE	
	<i>BRASS PRESS FITTINGS</i>	12
	2.3 RACCORDI ASSIALI	
	<i>BRASS AXIAL FITTINGS</i>	17
3	VALVOLE A SFERA	
	<i>BALL VALVES</i>	22
4	RUBINETTI	
	<i>TAPS</i>	26
	4.1 RUBINETTI SOTTOLAVABO	
	<i>ANGLE VALVE</i>	28
	4.2 RUBINETTI A SFERA	
	<i>BALL TAPS</i>	30
5	DOCCETTE	
	<i>SHATTAF</i>	31

1. PROFILO AZIENDALE

ITALIAN SHOWER SRL nasce nel 2013 dall'esperienza di oltre cinquant'anni nel settore idrotermosanitario del suo fondatore, Maggi Gianpietro. Dopo essere stato CEO di grosse aziende Bresciane del settore, è nato in lui il desiderio di creare questa nuova attività familiare che ha preso forma e si è delineata, affiancando esperienza a passione a concretezza e qualità e soprattutto MADE IN ITALY.

ITALIAN SHOWER SRL ha impostato la propria attività facendo una scelta ben precisa, tutta la produzione viene eseguita con attrezzature proprie, dagli stampi alla utensileria relativa ai singoli particolari dei raccordi a pressare, raccordi assiali, raccordi filettati, rubinetti e valvole a sfera sebbene collocati presso nostri affidati terzisti. Anche per quanto riguarda il mondo delle doccette, ci avvaliamo dello stesso principio.

Seguendo le esigenze di mercato e della propria clientela, la società si è evoluta orientandosi, oltretutto nella produzione della propria serie con marchio ALPI, verso la realizzazione articoli OEM, quindi a marchio.

1. COMPANY PROFILE

ITALIAN SHOWER SRL was founded in 2013 from the founder Maggi Gianpietro's, over fifty years of experience in the plumbing and heating sector. After serving as CEO of major companies in Brescia within the industry, he felt the desire to create this new family business, which took shape by combining experience, passion, practicality, quality, and, above all, MADE IN ITALY.

ITALIAN SHOWER SRL has structured its business around a very clear choice: all production is carried out with in-house equipment, from molds to the tools used for manufacturing the individual components of press fittings, axial fittings, threaded fittings, faucets, and ball valves, although the final stages are handled by trusted third-party contractors. The same approach applies to the world of shower heads.

In response to market demands and customer needs, the company has evolved, expanding its focus not only on producing its own ALPI-branded products but also on creating OEM items, manufactured under private labels.



1. PROFILO AZIENDALE

La soddisfazione del cliente è uno dei punti cardine dell'azienda, il nostro personale è sempre disponibile ad interloquire con i clienti, per progettare nuovi prodotti, ove richiesto, soddisfare richieste proprie del cliente ed implementare le famiglie di prodotti esistenti, al fine di garantire un prodotto eccellente.

L'ufficio tecnico e qualità controllano costantemente il materiale che viene lavorato e il personale qualificato, utilizzando appositi strumenti di misura e controllo di ultima generazione, certifica che il materiale risponda alle specifiche direttive interne che alle richieste del cliente.

ITALIAN SHOWER SRL certificandosi secondo la Norma di qualità UNI EN ISO 9001: 2015 vuole definire la naturale evoluzione di tutto il know-how, delle innovazioni e dell'impegno che sta mettendo a disposizione dei propri clienti.

1. COMPANY PROFILE

Customer satisfaction is one of the cornerstones of the company. Our staff is always available to engage with customers, whether to design new products when requested, meet specific customer requirements, or expand existing product lines, all with the goal of ensuring an excellent product.

The technical and quality departments continuously monitor the materials being processed. Qualified personnel, using advanced measuring and control instruments, certify that the materials comply with both the internal specifications and customer requirements.

By obtaining certification in accordance with the UNI EN ISO 9001:2015 Quality Standard, ITALIAN SHOWER SRL aims to define the natural evolution of its expertise, innovations, and the commitment it dedicates to its customers.





ITALIAN SHOWER

Water in Motion 

RACCORDI IN OTTONE A PRESSARE | BRASS PRESS FITTINGS



100% MADE IN ITALY | THE ITALIAN HIGH QUALITY



ITALIAN SHOWER

Water in Motion  

RACCORDI IN OTTONE FILETTATI

I raccordi in ottone della serie filettata sono progettati per essere utilizzati in molteplici ambiti, sia civile che industriale. Infatti sono idonei alla realizzazione di impianti idrosanitari sia con acqua calda che fredda, in impianti di riscaldamento/raffrescamento e per aria compressa.

Offrono diversi vantaggi: resistenza alla corrosione, durabilità, facilità d'installazione e versatilità.

E' disponibile un'ampia gamma di raccordi sia per quanto riguarda la figura che il diametro, inoltre possono essere forniti gialli sabbiati, nichelati o cromati.

BRASS THREADED FITTINGS

The brass fittings of the threaded series are designed to be used in multiple fields, both civil and industrial. In fact, they are suitable for the construction of hydro-sanitary systems with both hot and cold water, in heating/cooling systems, and for compressed air.

They offer several advantages: corrosion resistance, durability, ease of installation, and versatility.

A wide range of fittings is available in terms of both shape and diameter, and they can also be supplied in yellow sandblasted, nickel-plated, or chrome-plated finishes.



L'ALTA QUALITA' ITALIANA | THE ITALIAN HIGH QUALITY

2.1 RACCORDI IN OTTONE FILETTATO | 2.1 BRASS THREADED FITTINGS

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
PROLUNGHE M/F IN OTTONE <i>M/F BRASS EXTENSION</i> 	1/2" x 10 mm 1/2" x 15 mm 1/2" x 20 mm 1/2" x 25 mm 1/2" x 30 mm 1/2" x 40 mm 1/2" x 50 mm	GIALLO/YELLOW CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
NIPLO DOPPIO <i>DOUBLE NIPPLE</i> 	1/4" 3/8" 1/2" 3/4" 1" 1"1/4 1"1/2 2"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
NIPLO DOPPIO PROLUNGATO <i>LONG DOUBLE NIPPLE</i> 	1/2"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
NIPLO RIDOTTO <i>REDUCED NIPPLE</i> 	1/2" x 3/8" 3/4" x 1/2" 1" x 3/4" 1"1/4 x 1" 1"1/2 x 1"1/4 2" x 1"1/2	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
RIDUZIONE ESAGONALE M/F <i>M/F EXAGONAL BUSHING</i> 	1/2" x 3/8" 3/4" x 1/2" 1" x 3/4" 1"1/4 x 1" 1"1/2 x 1"1/4 2" x 1"1/2	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
TAPPO FEMMINA <i>FEMALE CAP</i> 	1/2" 3/4" 1" 1"1/4 1"1/2 2"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED

2.1 RACCORDI IN OTTONE FILETTATO | 2.1 BRASS THREADED FITTINGS

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
TAPPO MASCHIO MALE CAP 	1/2" 3/4" 1"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
TAPPO MASCHIO CON QUADRO MALE CAP WITH SQUARE 	1/2" 3/4" 1" 1"1/4	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
MANICOTTO SOCKET 	1/2" 3/4" 1" 1"1/4 1"1/2 2"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
MANICOTTO RIDOTTO REDUCED SOCKET 	1/2" x 3/8" 3/4" x 1/2" 1" x 3/4" 1"1/4 x 1" 1"1/2 x 1"1/4 2" x 1"1/2	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
PROLUNGA RIDOTTA F/M F/M REDUCED EXTENSION 	1/2" x 3/8" 3/4" x 1/2" 1" x 3/4"	GIALLO/YELLOW CROMATO/CHROME PLATED
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
GHIERA DI RIDUZIONE REDUCING RING 	1/2" x 3/8" 3/4" x 1/2" 1" x 3/4"	GIALLO/YELLOW CROMATO/CHROME PLATED

2.1 RACCORDI IN OTTONE FILETTATO | 2.1 BRASS THREADED FITTINGS

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
PORTAGOMMA MASCHIO <i>MALE HOSE CONNECTION</i> 	1/2" x 10 mm	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
	1/2" x 12 mm	
	1/2" x 14 mm	
	1/2" x 16 mm	
	1/2" x 20 mm	
	3/4" x 20 mm	
	3/4" x 25 mm	
	1" x 25 mm	
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
CONTRODADO <i>BACKNUT</i> 	1/2"	GIALLO/YELLOW CROMATO/CHROME PLATED
	3/4"	
	1"	
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
ANGOLO F/F <i>F/F ELBOW</i> 	1/4"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
	3/8"	
	1/2"	
	3/4"	
	1"	
	1"1/4	
	1"1/2	
	2"	

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
PORTAGOMMA FEMMINA <i>FEMALE HOSE CONNECTION</i> 	1/2" x 10 mm	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
	1/2" x 12 mm	
	1/2" x 14 mm	
	1/2" x 16 mm	
	1/2" x 20 mm	
	3/4" x 20 mm	
	3/4" x 25 mm	
	1" x 25 mm	
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
T FEMMINA <i>FEMALE TEE</i> 	1/4"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
	3/8"	
	1/2"	
	3/4"	
	1"	
	1"1/4	
	1"1/2	
	2"	
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
ANGOLO M/F CON FLANGIA <i>M/F ELBOW WITH WALLPLATE</i> 	1/4"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
	3/8"	
	1/2"	
	3/4"	
	1"	
	1"1/4	
	1"1/2	
	2"	

2.1 RACCORDI IN OTTONE FILETTATO | 2.1 BRASS THREADED FITTINGS

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
ANGOLO M/F <i>M/F ELBOW</i> 	1/4"	GIALLO/YELLOW NICHELATO/NICKEL PLATED CROMATO/CHROME PLATED
	3/8"	
	1/2"	
	3/4"	
	1"	
	1"1/4	
	1"1/2	
	2"	
ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
ANGOLO M/F 3 PEZZI CON SEDE O-RING <i>M/F ELBOW 3 PIECES WITH O-RING</i> 	1/2"	GIALLO/YELLOW NICHELATO/NICKEL PLATED
	3/4"	
	1"	

ARTICOLO ITEM	MISURA SIZE	FINITURA FINISHING
DRITTO M/F 3 PEZZI CON SEDE O-RING <i>M/F STRAIGHT FITTING 3 PIECES WITH O-RING</i> 	1/2"	GIALLO/YELLOW NICHELATO/NICKEL PLATED
	3/4"	
	1"	

RACCORDI IN OTTONE A PRESSARE

I raccordi in ottone a pressare sono progettati per il collegamento dei tubi multistrato e sono idonei alla realizzazione di impianti sia civili che industriali, ad esempio impianti idrosanitari, di riscaldamento a radiatori e a pannelli radianti, condizionamento e aria compressa. Possono essere utilizzati con i seguenti profili di ganasce: H, TH, U.

Grazie al montaggio dei raccordi a pressare viene garantito un collegamento sicuro e di qualità in tempi rapidi. Infatti, tramite pinza elettromeccanica e per mezzo di ganasce, viene pressata la bussola in acciaio AISI 304 garantendo una perfetta tenuta meccanica, mentre gli o-ring garantiscono la tenuta idraulica.

Le principali caratteristiche dei raccordi a pressare sono le seguenti: durata (la pressatura con pinze elettromeccaniche garantisce una perfetta tenuta nel tempo e di qualità ed inoltre tramite le finestre dell'anello in nylon è possibile verificare la corretta installazione), rapidità di installazione e versatilità.

BRASS PRESS FITTINGS

Brass press fittings are designed for connecting multilayer pipes and are suitable for both civil and industrial installations, such as hydro-sanitary systems, radiator and underfloor heating systems, air conditioning, and compressed air systems. They can be used with the following jaw profiles: H, TH, U.

Thanks to the installation of press fittings, a secure and high-quality connection is guaranteed in a short time. In fact, using an electromechanical press tool and jaws, the AISI 304 steel sleeve is pressed, ensuring a perfect mechanical seal, while the O-rings ensure hydraulic sealing.

The main characteristics of press fittings are as follows: durability (the pressing with electromechanical tools guarantees a perfect and long-lasting seal, and through the nylon ring windows, correct installation can be verified), quick installation, and versatility.



2.2 RACCORDI IN OTTONE A PRESSARE | 2.2 BRASS PRESS FITTINGS

ARTICOLO ITEM	MISURA SIZE
RACCORDO MASCHIO <i>MALE ADAPTOR</i> 	16 x 1/2"
	18 x 1/2"
	20 x 1/2"
	20 x 3/4"
	26 x 3/4"
	26 x 1"
	32 x 3/4"
	32 x 1"
	40 x 1"1/4
	50 x 1"1/2
	63 x 2"
ARTICOLO ITEM	MISURA SIZE
MANICOTTO <i>COUPLING</i> 	16 x 16
	18 x 18
	20 x 20
	26 x 26
	32 x 32
	40 x 40
	50 x 50
	63 x 63

ARTICOLO ITEM	MISURA SIZE
RACCORDO FEMMINA <i>FEMALE ADAPTOR</i> 	16 x 1/2"
	18 x 1/2"
	20 x 1/2"
	20 x 3/4"
	26 x 3/4"
	26 x 1"
	32 x 3/4"
	32 x 1"
	40 x 1"
	40 x 1"1/4
	50 x 1"1/2
	63 x 2"
ARTICOLO ITEM	MISURA SIZE
MANICOTTO DI RIDUZIONE <i>REDUCING COUPLING</i> 	20x16
	26x16
	26x20
	32x16
	32x20
	32x26
	40x20
	40x26
	40x32
	50x20
	50x26
	50x32
	50x40
	63x40
	63x50

2.2 RACCORDI IN OTTONE A PRESSARE | 2.2 BRASS PRESS FITTINGS

ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° <i>90° ELBOW</i> 	16 x 16 18 x 18 20 x 20 26 x 26 32 x 32 40 x 40 50 x 50 63 x 63
ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° CON DERIVAZIONE FEMMINA <i>90° ELBOW WITH THREADED FEMALE TAKE OFF</i> 	16 x 1/2" 18 x 1/2" 20 x 1/2" 20 x 3/4" 26 x 3/4" 26 x 1" 32 x 3/4" 32 x 1" 40 x 1"1/4 50 x 1"1/2

ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° CON DERIVAZIONE MASCHIO <i>90° ELBOW WITH THREADED MALE TAKE OFF</i> 	16 x 1/2" 16 x 3/4" 18 x 1/2" 20 x 1/2" 20 x 3/4" 26 x 3/4" 26 x 1" 32 x 3/4" 32 x 1"
ARTICOLO ITEM	MISURA SIZE
TEE A 90° <i>TEE A 90°</i> 	16 x 16 x 16 20 x 20 x 20 26 x 26 x 26 32 x 32 x 32 40 x 40 x 40 50 x 50 x 50 63 x 63 x 63

2.2 RACCORDI IN OTTONE A PRESSARE | 2.2 BRASS PRESS FITTINGS

ARTICOLO ITEM	MISURA SIZE
TEE A 90° CON DERIVAZIONE FEMMINA <i>90° TEE WITH THREADED FEMALE TAKE OFF</i> 	16 x 1/2" 18 x 1/2" 20 x 1/2" 20 x 3/4" 26 x 3/4" 32 x 3/4" 32 x 1" 40 x 1 1/4"
ARTICOLO ITEM	MISURA SIZE
TEE A 90° RIDOTTO <i>90° REDUCING TEE</i> 	20x16x16 40x26x40 20x16x20 40x32x40 20x20x16 50x26x50 26x16x26 50x32x50 26x16x16 50x40x50 26x26x16 63x40x63 26x20x20 63x50x63 26x20x26 26x26x20 32x20x20 32x20x32 32x26x26 32x26x32 32x32x20 32x32x26

ARTICOLO ITEM	MISURA SIZE
MURALE A GOMITO <i>WALL PLATE ELBOW</i> 	16 x 1/2" 18 x 1/2" 20 x 1/2" 20 x 3/4"
ARTICOLO ITEM	MISURA SIZE
DRITTO FEMMINA CON DADO GIREVOLE <i>FEMALE ADAPTOR WITH ROTATING NUT</i> 	16 x 1/2" 16 x 3/4" 18 x 1/2" 20 x 1/2" 20 x 3/4" 26 x 3/4" 26 x 1" 26 x 1"

2.2 RACCORDI IN OTTONE A PRESSARE | 2.2 BRASS PRESS FITTINGS

ARTICOLO ITEM	MISURA SIZE
DRITTO CON DADO GIREVOLE EUROKONO <i>DIRECT FITTING WITH ROTATING NUT EUROKONO</i>	16 x 3/4" 20 x 3/4"
	

ARTICOLO ITEM	MISURA SIZE
RUBINETTO AD INCASSO CON ROSONE <i>IN-WALL SHUT VALVE WITH ROSETTE</i>	16 x 16 20 x 20
	

RACCORDI IN OTTONE ASSIALI

I Raccordi assiali in ottone sono progettati per il collegamento dei tubi in polietilene reticolato (PEX) e in polietilene di elevata resistenza termica (PE-RT). I raccordi sono idonei sia per il passaggio di acqua calda che fredda in impianti idrico sanitari, impianti di riscaldamento a radiatori e pannelli radianti o sistemi di raffrescamento. Essi consentono la posa della tubazione sia a cielo aperto che sottotraccia. Grazie al montaggio dei raccordi assiali si realizza una connessione stabile a tenuta stagna, senza utilizzo di o-ring aggiuntivi, il quale non richiede manutenzione.

Il montaggio del tubo all'esterno del raccordo viene effettuato attraverso un'attrezzatura manuale di facile utilizzo, che attraverso uno svasatore "allarga" le estremità del tubo e lo calza sul raccordo. Il tubo sul raccordo viene poi serrato dalla presenza della bussola del diametro adeguato.

Le principali caratteristiche dei raccordi assiali sono le seguenti: durata nel tempo, maggior passaggio di acqua, resistenza alle alte temperature e versatilità.

BRASS AXIAL FITTINGS

Brass axial fittings are designed for connecting cross-linked polyethylene (PEX) pipes and high-temperature resistant polyethylene (PE-RT) pipes. The fittings are suitable for both hot and cold water in hydro-sanitary systems, radiator and underfloor heating systems, or cooling systems. They allow for the installation of piping both above ground and underground. Thanks to the installation of axial fittings, a stable and watertight connection is achieved without the use of additional O-rings, which does not require maintenance.

The installation of the pipe outside the fitting is carried out using an easy-to-use manual tool, which, through a reamer, "widens" the ends of the pipe and fits it onto the fitting. The pipe on the fitting is then tightened by the presence of the appropriately sized sleeve.

The main characteristics of axial fittings are as follows: durability over time, greater water flow, resistance to high temperatures, and versatility.



2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
BUSSOLA PER RACCORDI ASSIALI <i>SLEEVE FOR AXIAL FITTINGS</i>	16 20 25 32
	
ARTICOLO ITEM	MISURA SIZE
MANICOTTO DI RIDUZIONE <i>REDUCING COUPLING</i>	20 x 16 25 x 16 25 x 20 32 x 25 32 x 20
	

ARTICOLO ITEM	MISURA SIZE
MANICOTTO <i>COUPLING</i>	16 x 16 20 x 20 25 x 25 32 x 32
	
ARTICOLO ITEM	MISURA SIZE
RACCORDO MASCHIO <i>MALE ADAPTOR</i>	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 1/2" 25 x 3/4" 25 x 1" 32 x 3/4" 32 x 1"
	

2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
RACCORDO FEMMINA <i>FEMALE ADAPTOR</i> 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1" 32 x 3/4" 32 x 1"
ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° CON DERIVAZIONE FEMMINA <i>90° ELBOW WITH THREADED FEMALE TAKE OFF</i> 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1"

ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° CON DERIVAZIONE MASCHIO <i>90° ELBOW WITH THREADED MALE TAKE OFF</i> 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1"
ARTICOLO ITEM	MISURA SIZE
GOMITO A 90° <i>90° ELBOW</i> 	16 x 16 20 x 20 25 x 25 32 x 32

2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
TEE A 90° 90° TEE 	16 x 16 20 x 20 25 x 25 32 x 32
ARTICOLO ITEM	MISURA SIZE
TEE A 90° RIDOTTO 90° REDUCING TEE 	16 x 20 x 16 20 x 16 x 16 20 x 20 x 16 25 x 16 x 16 25 x 16 x 20 25 x 20 x 16 25 x 16 x 25 20 x 25 x 20 25 x 20 x 20 25 x 25 x 16 25 x 20 x 25 25 x 25 x 20 32 x 16 x 32 32 x 20 x 32 32 x 25 x 32

ARTICOLO ITEM	MISURA SIZE
TEE A 90° CON DERIVAZIONE FEMMINA 90° TEE WITH THREADED FEMALE TAKE OFF 	16 x 1/2" x 16 20 x 1/2" x 20 20 x 3/4" x 20 25 x 3/4" x 25
ARTICOLO ITEM	MISURA SIZE
RACCORDO MURALE A GOMITO WALL PLATE ELBOW FITTING 	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4"

2.3 RACCORDI IN OTTONE ASSIALI | 2.3 BRASS AXIAL FITTINGS

ARTICOLO ITEM	MISURA SIZE
RACCORDO FEMMINA CON DADO GIREVOLE FEMALE FITTING WITH ROTATING NUT	16 x 1/2" 16 x 3/4" 20 x 1/2" 20 x 3/4" 25 x 3/4" 25 x 1" 32 x 1"
	

ARTICOLO ITEM	MISURA SIZE
DRITTO CON DADO GIREVOLE EUROKONO DIRECT FITTING WITH ROTATING NUT EUROKONO	16 x 3/4" 20 x 3/4"
	



ITALIAN SHOWER

Water in Motion 

VALVOLE A SFERA | BALL VALVE



100% MADE IN ITALY | THE ITALIAN HIGH QUALITY

VALVOLE A SFERA

Le valvole a sfera in ottone a passaggio standard sono dispositivi di regolazione del flusso di fluidi, caratterizzate da una sfera con un foro centrale che ruota per aprire o chiudere il passaggio. L'ottone, un materiale resistente alla corrosione e durevole, conferisce a queste valvole un'ottima resistenza meccanica e termica.

Trovano impiego in diversi settori e applicazioni grazie alla loro versatilità e affidabilità. I principali campi di utilizzo sono: impianti idraulici (sia industriali che domestici), sistemi di riscaldamento e impianti di raffreddamento, sistemi di irrigazione, industria alimentare e chimica ecc.

Offrono diversi vantaggi, che le rendono una scelta popolare in molte applicazioni. Ecco alcuni dei principali benefici: affidabilità, facilità d'uso, versatilità, resistenza alla corrosione e facili installazioni.

BALL VALVES

Brass ball valves with standard passage are flow regulation devices characterized by a ball with a central hole that rotates to open or close the passage. Brass, a corrosion-resistant and durable material, gives these valves excellent mechanical and thermal resistance.

They are used in various sectors and applications due to their versatility and reliability. The main fields of use are: hydraulic systems (both industrial and domestic), heating and cooling systems, irrigation systems, food and chemical industries, etc. They offer several advantages, making them a popular choice in many applications. Here are some of the main benefits: reliability, ease of use, versatility, corrosion resistance, and easy installation.



3. VALVOLE A SFERA | 3. BALL VALVE

ARTICOLO ITEM		MISURA SIZE
	VALVOLA A SFERA M/F BOCCHETTONE CON MANIGLIA A FARFALLA <i>M/F STRAIGHT UNION BALL VALVE WITH BUTTERFLY</i>	1/2"
		3/4"
		1"
		1"1/4
		1"1/2
		2"
ARTICOLO ITEM		MISURA SIZE
	VALVOLA A SFERA F/F CON LEVA IN ACCIAIO O CON MANIGLIA A FARFALLA <i>F/F BALL VALVE WITH STEEL LEVER OR BUTTERFLY HANDLE</i>	1/2"
		3/4"
		1"
		1"1/4
		1"1/2
		2"
ARTICOLO ITEM		MISURA SIZE
	VALVOLA A SFERA M/F CON LEVA IN ACCIAIO O CON MANIGLIA A FARFALLA <i>M/F BALL VALVE WITH STEEL LEVER OR BUTTERFLY HANDLE</i>	1/2"
		3/4"
		1"
		1"1/4
		1"1/2
		2"

3. VALVOLE A SFERA | 3. BALL VALVE

ARTICOLO ITEM	MISURA SIZE
 MINIVALVOLA M/F CON MANIGLIA ROSSA O BLU <i>M/F MINI VALVE WITH RED OR BLUE HANDLE</i>	1/2" x 1/2"
ARTICOLO ITEM	MISURA SIZE
 VALVOLA A SFERA CON INSERTO PER TUBO PEX <i>BALL VALVE WITH NUT INSERT, NUT, O-RING FOR PEX PIPE</i>	16" x 1/2"



ITALIAN SHOWER

Water in Motion  

RUBINETTI | TAPS



100% MADE IN ITALY | THE ITALIAN HIGH QUALITY

RUBINETTI

TAPS

La nostra gamma di rubinetti si divide principalmente in:

- rubinetti sottolavabo:

sono realizzati in ottone cromato e sono dispositivi fondamentali per la gestione dell'acqua in questi ambienti. Possono essere mono-comando o bi-comando, a seconda che controllino la temperatura e il flusso dell'acqua con un'unica leva o con due manopole separate.

- rubinetti a sfera:

come le valvole a sfera, sono caratterizzati da una sfera con un foro centrale che ruota per aprire o chiudere il passaggio. L'ottone, un materiale resistente alla corrosione e durevole, conferisce a questi rubinetti un'ottima resistenza meccanica e termica. Fanno parte di questa categoria i rubinetti da giardino ed i rubinetti lavatrice.

Our range of taps is mainly divided into:

- angle-valve:

these are made of chrome-plated brass and are essential devices for water management in these environments. They can be single-handle or double-handle, depending on whether they control the temperature and flow of water with a single lever or with two separate knobs.

- ball taps:

like ball valves, they are characterized by a ball with a central hole that rotates to open or close the passage. Brass, a corrosion-resistant and durable material, gives these taps excellent mechanical and thermal resistance. This category includes garden taps and washing machine taps.



4.1 RUBINETTI SOTTOLAVABO | 4.1 ANGLE VALVES

ARTICOLO ITEM	MISURA SIZE
 RUBINETTO EXPORT CROMATO MANIGLIA CON TAPPO R/B <i>CHROME PLATED ANGLE VALVE EXPORT</i> <i>HANDLE R/B CAP</i>	1/2" x 1/2" 1/2" x 3/8"
ARTICOLO ITEM	MISURA SIZE
 RUBINETTO EXPORT CROMATO MANIGLIA "LUX" <i>CHROME PLATED ANGLE VALVE EXPORT</i> <i>HANDLE "LUX"</i>	1/2" x 1/2" 1/2" x 3/8"
ARTICOLO ITEM	MISURA SIZE
 RUBINETTO ECONOMY CROMATO MANIGLIA IN ABS <i>CHROME PLATED ANGLE VALVE ECONOMY</i> <i>ABS HANDLE</i>	1/2" x 1/2" 1/2" x 3/8"

4.1 RUBINETTI SOTTOLAVABO | 4.1 ANGLE VALVES

ARTICOLO ITEM	MISURA SIZE
 RUBINETTO ECONOMY LUNGO CROMATO MANIGLIA IN ABS <i>CHROME PLATED LONG ANGLE VALVE ECONOMY</i> <i>ABS HANDLE</i>	1/2" x 1/2" 1/2" x 3/8"
ARTICOLO ITEM	MISURA SIZE
 RUBINETTO A 5 VIE CROMATO MANIGLIE IN ABS <i>CHROME PLATED DOUBLE EXIT ANGLE VALVE</i> <i>ABS HANDLES</i>	1/2" x 1/2" x 1/2"

4.2 RUBINETTI A SFERA | 4.2 BALL TAPS

ARTICOLO ITEM	MISURA SIZE
 RUBINETTO GIARDINO STANDARD <i>STANDARD GARDEN BIBCOCK</i>	1/2" x 1/2"
ARTICOLO ITEM	MISURA SIZE
 RUBINETTO LAVATRICE <i>WASHING MACHINE VALVE</i>	1/2" x 3/4"



ITALIAN SHOWER

Water in Motion 

DOCETTE | SHATTAF



100% MADE IN ITALY | THE ITALIAN HIGH QUALITY

DOCETTE

Le doccette sono piccole docce in plastica che vengono fornite con un tubo in pvc rinforzato.

Agli estremi del tubo vengono applicati degli elementi quali una ghiera ed una calotta in ottone cromato e zigrinate, due codoli e due cartelle in ottone.

Il kit completo prevede anche un supporto a muro con relativi tasselli, viti e due o-ring.

Tutti questi elementi sono realizzati con materiale di origine italiana.

SHATTAF

Shattaf are small plastic showers that are furnished with a reinforced PVC hose.

At the ends of the hose, elements such as a knurled chrome-plated brass ring and cap, two nipples, and two brass plates are applied.

The complete kit also includes a wall support with related plugs and screws and two O-rings.

All these elements are made from Italian-origin materials.



DOCETTE | SHATTAF

ARTICOLO | ITEM



DOCETTA BIANCA STANDARD
WHITE STANDARD SHATTAF

DOCETTA BIANCA GIREVOLE
WHITE SHATTAF ANTI-TWIST

ARTICOLO | ITEM

DOCETTA CROMATA STANDARD
CHROMED STANDARD SHATTAF

DOCETTA CROMATA GIREVOLE
CHROMED SHATTAF ANTI-TWIST





ITALIAN SHOWER

Water in Motion 

Italian Shower Srl

Via Edison, 27 - 27/a
25050 Provaglio d'Iseo (BS) - Italy

P.iva e C.F. 03524420985

Tel. +39 030/6950257 | Fax +39 030/6950258

Informazioni: info@italianshower.com

Export: export@italianshower.com

PEC: italianshower@legalmail.it

www.italianshower.com

www.italianshower.it

